Bjerring Krakus Teater-, biograf- og konferencestole



BJERRING

Descriptions

BJERRING

- A ‡ame-retardant fabric and polyurethane foam of high quality provide adequate support for the back and ensure seating comfort for many hours.
- The rear backrest is made of the highest quality ergonomically profiled multi-layer ply wood.

- The upholstered seat cushion fll led with foam moulded into a mould by means of injection mo ulding technology, which ensures high resistance to the deforma tion of the foam.
- The cover of the seat made of high-grade multi-layer plywood lacquered or upholstered.



- The upholstered seat cushion filled with foam injected into a mould by means of injection moulding technology, which ensures high resistance to the deformation of the foam.
- The sides of the seat in the form of two prisms forming a low rec tangle made of high-grade mul ti-layer plywood.

Additional options

BJERRING



Cassette
stable made of solid wood combi ned with high quality multi-layered
plywood, mounted on the arm.



a modern shape mechanism with the option of fltting the cover colored in any RAL color, mounted on the back.



Seat with a perforated cover.



Fully upholstered seat.



Wooden leg fully upholstered.



Seat and row numbering in the form of plates or computer embro - idery at any position.





Front panel
Robust self-contained steel construc tion with built-in cassette which contains a writing table, the whole forming
a closed entity.

Technical data


overall height (mm)	width between the axes (mm)	seat height when unfolded (mm)	depth of the chair when folded (mm)
900 - 1100	500 - 600	430 - 450	A) 390 - 450 B) 440 - 500


A) standard version





B) cassette version







C/ front panel

